

LOGO! DM8 230R expansion module, PS/I/O: 230V/230V/relay, 2 MW, 4 DI/4 DO for LOGO! 8



Installation type/mounting

Mounting on 35 mm DIN rail, 2 spacing units wide

Supply voltage

Rated value (DC)

- 115 V DC Yes
- 230 V DC Yes

permissible range, lower limit (DC) 100 V

permissible range, upper limit (DC) 253 V

Rated value (AC)

- 115 V AC Yes
- 230 V AC Yes

Line frequency

- permissible range, lower limit 47 Hz
- permissible range, upper limit 63 Hz

Digital inputs

Number of digital inputs 4

Input voltage

- Type of input voltage AC/DC

<ul style="list-style-type: none"> • for signal "0" • for signal "1" 	<p>< 40 V AC, < 30 V DC</p> <p>> 79 V AC, > 79 V DC</p>
Input current	
<ul style="list-style-type: none"> • for signal "0", max. (permissible quiescent current) • for signal "1", typ. 	<p>0.06 mA; 0.05 mA with AC, 0.06 mA with DC</p> <p>0.13 mA</p>
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	40 ms
— at "1" to "0", max.	75 ms
Digital outputs	
Number of digital outputs	4; Relays
Short-circuit protection	No
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • on lamp load, max. 	1 000 W; 500 W at 115V AC
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value • for signal "1" minimum load current 	<p>5 A</p> <p>100 mA</p>
Parallel switching of two outputs	
<ul style="list-style-type: none"> • for uprating 	No
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. • with inductive load, max. • mechanical, max. 	<p>2 Hz</p> <p>0.5 Hz</p> <p>10 Hz</p>
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	5 A
EMC	
Emission of radio interference acc. to EN 55 011	
<ul style="list-style-type: none"> • Limit class B, for use in residential areas 	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> • IP20 	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes

according to VDE 0631	Yes
Marine approval	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C; ES03 and higher: -20 °C
• max.	55 °C
Dimensions	
Width	35.5 mm
Height	90 mm
Depth	58 mm
last modified:	08/27/2019