

LOGO! CSM 230 Compact Switch Module of connection of a LOGO! (... 0BA7) and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s; unmanaged switch, 4 RJ45 ports, 1x front port for diagnostics AC/DC 115 ... 240 V



Product type designation	LOGO! CSM 230
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
• for network components or terminal equipment	4
Number of 100 Mbit/s SC ports	
• for multimode	0
Number of 1000 Mbit/s LC ports	
• for multimode	0
• for single mode (LD)	0
Interfaces / others	
Number of electrical connections	
• for power supply	1
Type of electrical connection	
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	

Type of voltage / of the supply voltage	115...240 V AC/DC
Supply voltage	
<ul style="list-style-type: none"> external 	230 V
<ul style="list-style-type: none"> external / minimum 	100 V
<ul style="list-style-type: none"> external / maximum 	240 V
Product component / fusing at power supply input	Yes
Consumed current / maximum	0.02 A
Power loss [W]	
<ul style="list-style-type: none"> at AC / at 230 V 	1.8 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 55 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	90 %
Protection class IP	IP20

Design, dimensions and weight

Design	LOGO! module
Width	72 mm
Height	90 mm
Depth	55 mm
Net weight	0.155 kg
Mounting type	
<ul style="list-style-type: none"> 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> wall mounting 	Yes
<ul style="list-style-type: none"> S7-300 rail mounting 	No
<ul style="list-style-type: none"> S7-1500 rail mounting 	No

Product functions / management, configuration

Product function	
<ul style="list-style-type: none"> multiport mirroring 	No
Product function / switch-managed	No

Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> for FM 	FM3600 and 3611: CL I, Div2, Group A,B,C,D T4, CL I, Zone 2, Group IIC, T4, Ta=55°C
<ul style="list-style-type: none"> for hazardous zone 	no
<ul style="list-style-type: none"> for safety / from CSA and UL 	UL60079-0, UL60079-15, CSA C22.2

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
---	-----

Standards, specifications, approvals / miscellaneous

Certificate of suitability

- | | |
|---------------|-----|
| • C-Tick | Yes |
| • KC approval | No |

Standards, specifications, approvals / ship classification

Marine classification association

- | | |
|---|----|
| • American Bureau of Shipping Europe Ltd. (ABS) | No |
| • Bureau Veritas (BV) | No |
| • Det Norske Veritas (DNV) | No |
| • Germanische Lloyd (GL) | No |
| • Lloyds Register of Shipping (LRS) | No |
| • Nippon Kaiji Kyokai (NK) | No |
| • Polski Rejestr Statkow (PRS) | No |

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

08/27/2019