

SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A, 2 AI 0-10 V DC, 2 AO 0-20 mA DC, Power supply: DC 20.4-28.8 V DC, Program/data memory 125 KB



| General information   |  |
|---|--|
| Product type designation  | CPU 1215C DC/DC/relay                    |
| Firmware version  | V4.2                                     |
| Engineering with  |  |
| <ul style="list-style-type: none"> <li>Programming package</li> </ul>                 | STEP 7 V14 or higher                     |
| Supply voltage  |  |
| Rated value (DC)  |  |
| <ul style="list-style-type: none"> <li>24 V DC</li> </ul>                             | Yes                                      |
| permissible range, lower limit (DC)   | 20.4 V                                   |
| permissible range, upper limit (DC)   | 28.8 V                                   |
| Reverse polarity protection   | Yes                                      |
| Load voltage L+   |  |
| <ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>                    | 24 V                                     |
| <ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul> | 20.4 V                                   |
| <ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul> | 28.8 V                                   |
| Input current   |  |
| Current consumption (rated value)   | 500 mA; CPU only                         |
| Current consumption, max.   | 1 500 mA; CPU with all expansion modules |

|   |   |
|---|---|
| Inrush current, max.                                      | 12 A; at 28.8 V DC  |
| $I^2t$  | 0.8 A <sup>2</sup> ·s   |
| <b>Output current</b>                                     |   |
| for backplane bus (5 V DC), max.                          | 1 600 mA; Max. 5 V DC for SM and CM   |
| <b>Encoder supply</b>                                     |   |
| 24 V encoder supply                                       |   |
| • 24 V  | L+ minus 4 V DC min.  |
| <b>Power loss</b>   |   |
| Power loss, typ.  | 12 W  |
| <b>Memory</b>   |   |
| Work memory   |   |
| • integrated  | 125 kbyte   |
| • expandable  | No  |
| Load memory   |   |
| • integrated  | 4 Mbyte   |
| • Plug-in (SIMATIC Memory Card), max.                     | with SIMATIC memory card  |
| Backup  |   |
| • present   | Yes   |
| • maintenance-free  | Yes   |
| • without battery   | Yes   |
| <b>CPU processing times</b>                               |   |
| for bit operations, typ.                                  | 0.08 µs; / instruction  |
| for word operations, typ.                                 | 1.7 µs; / instruction   |
| for floating point arithmetic, typ.                       | 2.3 µs; / instruction   |
| <b>CPU-blocks</b>   |   |
| Number of blocks (total)                                  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB  |   |
| • Number, max.  | Limited only by RAM for code  |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte  |
| Flag  |   |
| • Number, max.  | 8 kbyte; Size of bit memory address area  |
| Local data  |   |
| • per priority class, max.                                | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB   |
| <b>Address area</b>                                       |   |
| Process image   |   |

- Inputs, adjustable
- Outputs, adjustable

1 kbyte

1 kbyte

### Hardware configuration

Number of modules per system, max.

3 comm. modules, 1 signal board, 8 signal modules

### Time of day

Clock

- Hardware clock (real-time)
- Backup time
- Deviation per day, max.

Yes

480 h; Typical

±60 s/month at 25 °C

### Digital inputs

Number of digital inputs

14; Integrated

- of which inputs usable for technological functions

6; HSC (High Speed Counting)

Source/sink input

Yes

Number of simultaneously controllable inputs

all mounting positions

— up to 40 °C, max.

14

Input voltage

- Rated value (DC)
- for signal "0"
- for signal "1"

24 V

5 V DC at 1 mA

15 V DC at 2.5 mA

Input delay (for rated value of input voltage)

for standard inputs

— parameterizable

Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four

— at "0" to "1", min.

0.2 ms

— at "0" to "1", max.

12.8 ms

for interrupt inputs

— parameterizable

Yes

for technological functions

— parameterizable

Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz

Cable length

- shielded, max.
- unshielded, max.

500 m; 50 m for technological functions

300 m; for technological functions: No

### Digital outputs

Number of digital outputs

10; Relays

Switching capacity of the outputs

- with resistive load, max.
- on lamp load, max.

2 A

30 W with DC, 200 W with AC

Output delay with resistive load

|   |  |
|---|--|
| • "0" to "1", max.  | 10 ms; max.  |
| • "1" to "0", max.  | 10 ms; max.  |
| <b>Relay outputs</b>  |  |
| • Number of relay outputs                                     | 10   |
| • Number of operating cycles, max.                            | mechanically 10 million, at rated load voltage 100 000 |
| <b>Cable length</b>   |  |
| • shielded, max.  | 500 m  |
| • unshielded, max.  | 150 m  |
| <b>Analog inputs</b>  |  |
| Number of analog inputs                                       | 2  |
| <b>Input ranges</b>   |  |
| • Voltage   | Yes  |
| <b>Input ranges (rated values), voltages</b>                  |  |
| • 0 to +10 V  | Yes  |
| • Input resistance (0 to 10 V)                                | ≥100k ohms   |
| <b>Cable length</b>   |  |
| • shielded, max.  | 100 m; twisted and shielded                            |
| <b>Analog outputs</b>   |  |
| Number of analog outputs                                      | 2  |
| <b>Output ranges, current</b>                                 |  |
| • 0 to 20 mA  | Yes  |
| <b>Analog value generation for the inputs</b>                 |  |
| <b>Integration and conversion time/resolution per channel</b> |  |
| • Resolution with overrange (bit including sign), max.        | 10 bit   |
| • Integration time, parameterizable                           | Yes  |
| • Conversion time (per channel)                               | 625 μs   |
| <b>Analog value generation for the outputs</b>                |  |
| <b>Integration and conversion time/resolution per channel</b> |  |
| • Resolution with overrange (bit including sign), max.        | 10 bit   |
| <b>Encoder</b>  |  |
| <b>Connectable encoders</b>                                   |  |
| • 2-wire sensor   | Yes  |
| <b>1. Interface</b>   |  |
| Interface type  | PROFINET   |
| Physics   | Ethernet   |
| Isolated  | Yes  |
| automatic detection of transmission rate                      | Yes  |
| Autonegotiation   | Yes  |

|   |   |
|---|---|
| Autocrossing  | Yes   |
| <b>Interface types</b>  |   |
| • Number of ports   | 2   |
| • integrated switch   | Yes   |
| <b>Protocols</b>  |   |
| • PROFINET IO Controller  | Yes   |
| • PROFINET IO Device  | Yes   |
| • SIMATIC communication   | Yes   |
| • Open IE communication   | Yes   |
| • Web server  | Yes   |
| • Media redundancy  | Yes; as MRP client  |
| <b>PROFINET IO Controller</b>   |   |
| • Transmission rate, max.   | 100 Mbit/s  |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — S7 routing  | Yes   |
| — Isochronous mode  | No  |
| — Open IE communication   | Yes   |
| — IRT   | No  |
| — MRP   | Yes; as MRP client  |
| — MRPD  | No  |
| — PROFINergy  | No  |
| — Prioritized startup   | Yes   |
| — Number of IO devices with prioritized startup, max.                         | 16  |
| — Number of connectable IO Devices, max.                                      | 16  |
| — Number of connectable IO Devices for RT, max.                               | 16  |
| — of which in line, max.  | 16  |
| — Activation/deactivation of IO Devices                                       | Yes   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8   |
| — Updating time   | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| <b>PROFINET IO Device</b>   |   |
| <b>Services</b>   |   |
| — PG/OP communication   | Yes   |
| — S7 routing  | Yes   |
| — Isochronous mode  | No  |
| — Open IE communication   | Yes   |
| — IRT   | No  |

|   |                    |
|---|--------------------|
| — MRP   | Yes; as MRP client |
| — MRPD  | No                 |
| — PROFINergy  | Yes                |
| — Shared device                                     | Yes                |
| — Number of IO Controllers with shared device, max. | 2                  |

## Protocols

|                                   |   |
|-----------------------------------|---|
| Supports protocol for PROFINET IO | Yes   |
| PROFIBUS                          | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required |
| AS-Interface                      | Yes; CM 1243-2 required                               |

### Protocols (Ethernet)

|          |     |
|----------|-----|
| • TCP/IP | Yes |
| • DHCP   | No  |
| • SNMP   | Yes |
| • DCP    | Yes |
| • LLDP   | Yes |

### Open IE communication

|                        |            |
|------------------------|------------|
| • TCP/IP               | Yes        |
| — Data length, max.    | 8 kbyte    |
| • ISO-on-TCP (RFC1006) | Yes        |
| — Data length, max.    | 8 kbyte    |
| • UDP                  | Yes        |
| — Data length, max.    | 1 472 byte |

### Web server

|                         |     |
|-------------------------|-----|
| • supported             | Yes |
| • User-defined websites | Yes |

### Further protocols

|          |     |
|----------|-----|
| • MODBUS | Yes |
|----------|-----|

## Communication functions

### S7 communication

|                           |  |
|---------------------------|--|
| • supported               | Yes  |
| • as server               | Yes  |
| • as client               | Yes  |
| • User data per job, max. | See online help (S7 communication, user data size) |

### Number of connections

|           |                 |
|-----------|-----------------|
| • overall | 16; dynamically |
|-----------|-----------------|

## Test commissioning functions

### Status/control

|                           |  |
|---------------------------|--|
| • Status/control variable | Yes  |
| • Variables               | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |

| Forcing   |                      |
|---|----------------------|
| • Forcing   | Yes                  |
| Diagnostic buffer   |                      |
| • present   | Yes                  |
| Traces  |                      |
| • Number of configurable Traces   | 2                    |
| • Memory size per trace, max.   | 512 kbyte            |
| Interrupts/diagnostics/status information   |                      |
| Diagnostics indication LED  |                      |
| • RUN/STOP LED  | Yes                  |
| • ERROR LED   | Yes                  |
| • MAINT LED   | Yes                  |
| Integrated Functions  |                      |
| Number of counters  | 6                    |
| Counting frequency (counter) max.   | 100 kHz              |
| Frequency measurement   | Yes                  |
| controlled positioning  | Yes                  |
| Number of position-controlled positioning axes, max.                                  | 8                    |
| Number of positioning axes via pulse-direction interface                              | Up to 4 with SB 1222 |
| PID controller  | Yes                  |
| Number of alarm inputs  | 4                    |
| Potential separation  |                      |
| Potential separation digital inputs   |                      |
| • Potential separation digital inputs   | 500V AC for 1 minute |
| • between the channels, in groups of  | 1                    |
| Potential separation digital outputs  |                      |
| • Potential separation digital outputs  | Relays               |
| • between the channels  | No                   |
| • between the channels, in groups of  | 2                    |
| EMC   |                      |
| Interference immunity against discharge of static electricity                         |                      |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes                  |
| — Test voltage at air discharge   | 8 kV                 |
| — Test voltage at contact discharge   | 6 kV                 |
| Interference immunity to cable-borne interference                                     |                      |
| • Interference immunity on supply lines acc. to IEC 61000-4-4                         | Yes                  |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                        | Yes                  |

|  |   |
|--|---|
| <b>Interference immunity against voltage surge</b>   |   |
| • on the supply lines acc. to IEC 61000-4-5  | Yes   |
| <b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b> |   |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                       | Yes   |
| <b>Emission of radio interference acc. to EN 55 011</b>  |   |
| • Limit class A, for use in industrial areas   | Yes; Group 1  |
| • Limit class B, for use in residential areas  | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011  |
| <b>Degree and class of protection</b>  |   |
| Degree of protection acc. to EN 60529  |   |
| • IP20   | Yes   |
| <b>Standards, approvals, certificates</b>  |   |
| CE mark  | Yes   |
| UL approval  | Yes   |
| cULus  | Yes   |
| FM approval  | Yes   |
| RCM (formerly C-TICK)  | Yes   |
| KC approval  | Yes   |
| Marine approval  | Yes   |
| <b>Ambient conditions</b>  |   |
| Free fall  |   |
| • Fall height, max.  | 0.3 m; five times, in product package   |
| Ambient temperature during operation   |   |
| • min.   | -20 °C  |
| • max.   | 60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical |
| • horizontal installation, min.  | -20 °C  |
| • horizontal installation, max.  | 60 °C   |
| • vertical installation, min.  | -20 °C  |
| • vertical installation, max.  | 50 °C   |
| Ambient temperature during storage/transportation  |   |
| • min.   | -40 °C  |
| • max.   | 70 °C   |
| Air pressure acc. to IEC 60068-2-13  |   |
| • Operation, min.  | 795 hPa   |
| • Operation, max.  | 1 080 hPa   |
| • Storage/transport, min.  | 660 hPa   |
| • Storage/transport, max.  | 1 080 hPa   |
| Altitude during operation relating to sea level  |   |
| • Installation altitude, min.  | -1 000 m  |



|   |   |
|---|---|
| • Installation altitude, max.                                 | 2 000 m   |
| <b>Relative humidity</b>                                      |   |
| • Operation, max.   | 95 %; no condensation   |
| <b>Vibrations</b>   |   |
| • Vibration resistance during operation acc. to IEC 60068-2-6 | 2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail                   |
| • Operation, tested according to IEC 60068-2-6                | Yes   |
| <b>Shock testing</b>  |   |
| • tested according to IEC 60068-2-27                          | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| <b>Pollutant concentrations</b>                               |   |
| • SO <sub>2</sub> at RH < 60% without condensation            | SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free      |
| <b>Configuration</b>  |   |
| <b>Programming</b>  |   |
| Programming language  |   |
| — LAD   | Yes   |
| — FBD   | Yes   |
| — SCL   | Yes   |
| <b>Know-how protection</b>                                    |   |
| • User program protection/password protection                 | Yes   |
| • Copy protection   | Yes   |
| • Block protection  | Yes   |
| <b>Access protection</b>                                      |   |
| • Protection level: Write protection                          | Yes   |
| • Protection level: Read/write protection                     | Yes   |
| • Protection level: Complete protection                       | Yes   |
| <b>Cycle time monitoring</b>                                  |   |
| • adjustable  | Yes   |
| <b>Dimensions</b>   |   |
| Width   | 130 mm  |
| Height  | 100 mm  |
| Depth   | 75 mm   |
| <b>Weights</b>  |   |
| Weight, approx.   | 585 g   |
| <b>last modified:</b>   | 08/27/2019  |