

SIMATIC S7-1200, Digital input SB 1221, 4 DI, 24 V DC 200 kHz,
Sourcing input



Figure similar

General information

Product type designation SB 1221, DI 4x24 V DC 200 kHz

Input current

from backplane bus 5 V DC, typ. 40 mA

Power loss

Power loss, typ. 1 W

Digital inputs

Number of digital inputs 4; Current-sourcing

- in groups of 4

Input voltage

- Type of input voltage DC
- Rated value (DC) 24 V
- for signal "0" (L+ minus 5.0 V DC) ... L+ (1.4 ... 0 mA)
- for signal "1" 0 V ... (L+ minus 10 V DC (10 ... 2.9 mA))

Input current

• for signal "0", max. (permissible quiescent current)	1.4 mA
• for signal "1", min.	2.9 mA
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 μ s; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	Yes
Cable length	
• shielded, max.	50 m; shielded, twisted pair
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• for status of the inputs	Yes
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Storage/transport, min.	660 hPa

• Storage/transport, max.	1 080 hPa
---------------------------	-----------

Relative humidity

• Operation at 25 °C without condensation, max.	95 %
---	------

Mechanics/material

Enclosure material (front)

• Plastic	Yes
-----------	-----

Dimensions

Width	38 mm
-------	-------

Height	62 mm
--------	-------

Depth	21 mm
-------	-------

Weights

Weight, approx.	35 g
-----------------	------

last modified:	08/27/2019
-----------------------	------------