

SIMATIC S7-1200, Digital output SM 1222, 8 DO, Relay Changeover contact



### General information

Product type designation	SM 1222, DQ 8x relay/2 A
--------------------------	--------------------------

### Supply voltage

permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

### Input current

from backplane bus 5 V DC, max.	140 mA
---------------------------------	--------

### Digital outputs

<ul style="list-style-type: none"> <li>from load voltage L+, max.</li> </ul>	16.7 mA/relay coil
--	--------------------

### Power loss

Power loss, typ.	5 W
------------------	-----

### Digital outputs

Number of digital outputs	8
<ul style="list-style-type: none"> <li>in groups of</li> </ul>	1
Short-circuit protection	No; to be provided externally

### Switching capacity of the outputs

<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	2 A
---	-----

• on lamp load, max.	30 W with DC, 200 W with AC
<b>Output voltage</b>	
• Rated value (DC)	5 V DC to 30 V DC
• Rated value (AC)	5 V AC to 250 V AC
<b>Output current</b>	
• for signal "1" rated value	2 A
<b>Output delay with resistive load</b>	
• "0" to "1", max.	10 ms
• "1" to "0", max.	10 ms
<b>Total current of the outputs (per group)</b>	
horizontal installation	
— up to 50 °C, max.	2 A; Current per mass
<b>Relay outputs</b>	
• Number of relay outputs	8
• Rated supply voltage of relay coil L+ (DC)	24 V
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
<b>Switching capacity of contacts</b>	
— with inductive load, max.	2 A
— on lamp load, max.	30 W with DC, 200 W with AC
— with resistive load, max.	2 A
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostics indication LED</b>	
• for status of the outputs	Yes
<b>Potential separation</b>	
<b>Potential separation digital outputs</b>	
• between the channels	Relays
• between the channels, in groups of	1
• between the channels and backplane bus	1500 V AC for 1 minute
<b>Permissible potential difference</b>	
between different circuits	750 V AC for 1 minute
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes

UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes

### Ambient conditions

#### Free fall

- Fall height, max. 0.3 m; five times, in product package

#### Ambient temperature during operation

- min. -20 °C
- max. 60 °C; Number of simultaneously activated outputs: 4 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 8 at 55 °C horizontal or 45 °C vertical
- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C
- permissible temperature change 5°C to 55°C, 3°C / minute

#### Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

#### Air pressure acc. to IEC 60068-2-13

- Storage/transport, min. 660 hPa
- Storage/transport, max. 1 080 hPa

#### Relative humidity

- Operation at 25 °C without condensation, max. 95 %

### Connection method

required front connector	Yes
--------------------------	-----

### Mechanics/material

Enclosure material (front)	
• Plastic	Yes

### Dimensions

Width	70 mm
Height	100 mm
Depth	75 mm

### Weights

Weight, approx.	310 g
-----------------	-------

**last modified:** 08/27/2019