

Product type designation

CP 1243-7 LTE US

Communications processor CP 1243-7 LTE US for Connection of SIMATIC S7-1200 to LTE network in American frequency band



Transmission rate

Transfer rate

- for LTE transmission
 - with downlink / maximum 42 Mbit/s
 - with uplink / maximum 5.76 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
<ul style="list-style-type: none"> • for external antenna(s) 1 • for power supply 1 	
Number of slots	
<ul style="list-style-type: none"> • for SIM cards 1 	
Type of electrical connection	
<ul style="list-style-type: none"> • for external antenna(s) SMA socket (50 ohms) • for power supply 3-pole terminal block 	
Slot version	
<ul style="list-style-type: none"> • for SIM card Standard 	

Wireless technology

Type of mobile wireless service	
<ul style="list-style-type: none"> • is supported / SMS 	Yes
<ul style="list-style-type: none"> • is supported / GPRS 	Yes
<ul style="list-style-type: none"> • Note 	GPRS (Multislot Class 10)
Type of mobile network / is supported	
<ul style="list-style-type: none"> • GSM 	Yes
<ul style="list-style-type: none"> • UMTS 	Yes
<ul style="list-style-type: none"> • LTE 	Yes
Operating frequency	
<ul style="list-style-type: none"> • 850 MHz 	Yes
<ul style="list-style-type: none"> • 1900 MHz 	Yes
Operating frequency	
<ul style="list-style-type: none"> • for LTE transmission / 700 MHz 	Yes
<ul style="list-style-type: none"> • for LTE transmission / 1700 MHz 	Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	20 %
Consumed current	
<ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / typical 	0.1 A
<ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / maximum 	0.22 A

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • for vertical installation / during operation 	-20 ... +60 °C
<ul style="list-style-type: none"> • for horizontally arranged busbars / during operation 	-20 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm
Depth	75 mm

Net weight	0.133 kg
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	No
<ul style="list-style-type: none"> • wall mounting 	Yes

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> • per CPU / maximum 	3

Performance data

Number of users/telephone numbers / definable / maximum	10
---	----

Performance data / open communication

Number of possible connections / for open communication	
<ul style="list-style-type: none"> • by means of T blocks / maximum 	like CPU

Performance data / IT functions

Number of possible connections	
<ul style="list-style-type: none"> • as e-mail client / maximum 	1

Performance data / telecontrol

Suitability for use	
<ul style="list-style-type: none"> • substation 	Yes
Control center connection	Telecontrol Server Basic supported
<ul style="list-style-type: none"> • by means of a permanent connection 	supported
<ul style="list-style-type: none"> • by means of demand-oriented connection 	supported
<ul style="list-style-type: none"> • Note 	Connection to SCADA system using OPC interface
Protocol / is supported	
<ul style="list-style-type: none"> • DNP3 	No
<ul style="list-style-type: none"> • IEC 60870-5 	No
Product function / data buffering if connection is aborted	Yes
Number of stations / for direct communication / with Telecontrol Server Basic	
<ul style="list-style-type: none"> • in send direction / maximum 	3
<ul style="list-style-type: none"> • in receive direction / maximum 	15

Performance data / Teleservice

Diagnostics function / online diagnostics with SIMATIC STEP 7	Yes
Product function	
<ul style="list-style-type: none"> • program download with SIMATIC STEP 7 	Yes
<ul style="list-style-type: none"> • Remote firmware update 	Yes

Product functions / management, configuration	
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 Basic/Professional
Product functions / Diagnosis	
Product function / Web-based diagnostics	Yes
Product functions / Security	
Firewall version	stateful inspection
Product function / with VPN connection	IPsec, SINEMA RC
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1
Number of possible connections / with VPN connection	1
Product function	
<ul style="list-style-type: none"> • password protection for teleservice access 	Yes
<ul style="list-style-type: none"> • encrypted data transmission 	Yes
Product functions / Time	
Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
time synchronization	
<ul style="list-style-type: none"> • from control center 	Yes
Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
Security information	

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

08/26/2019