



SIMATIC S7-1500 Compact CPU CPU 1512C-1 PN, central processing unit with working memory 250 KB for program and 1 MB for data, 32 digital inputs, 32 digital outputs, 5 analog inputs, 2 analog outputs, 6 high speed counters, 4 high speed outputs for PTO/PWM/frequency output 1. interface: PROFINET IRT with 2 port switch, 48 NS bit-performance, incl. front connector push-in, SIMATIC memory card necessary

| General information                                       |  |
|---|--|
| Product type designation                                  | CPU 1512C-1 PN   |
| HW functional status                                      | FS01   |
| Firmware version  | V2.6   |
| Product function  |  |
| • I&M data  | Yes; I&M0 to I&M3  |
| Engineering with  |  |
| • STEP 7 TIA Portal configurable/integrated as of version | V15.1 (FW V2.6) / V15 (FW V2.5) or higher; with older TIA Portal versions configurable as 6ES7512-1CK00-0AB0 |
| Configuration control                                     |  |
| via dataset   | Yes  |
| Display   |  |
| Screen diagonal [cm]                                      | 3.45 cm  |
| Control elements  |  |
| Number of keys  | 8  |
| Mode buttons  | 2  |
| Supply voltage  |  |

|  |   |
|--|---|
| Type of supply voltage   | 24 V DC   |
| permissible range, lower limit (DC)  | 19.2 V; 20.4 V DC, for supplying the digital inputs/outputs |
| permissible range, upper limit (DC)  | 28.8 V  |
| Reverse polarity protection  | Yes   |
| <b>Mains buffering</b>   |   |
| <ul style="list-style-type: none"> <li>• Mains/voltage failure stored energy time</li> <li>• Repeat rate, min.</li> </ul>    | 5 ms; Refers to the power supply on the CPU section<br>1/s  |
| <b>Input current</b>   |   |
| Current consumption (rated value)  | 0.8 A; Without load; 18.8 A: CPU + load                     |
| Current consumption, max.  | 1 A; Without load; 19 A: CPU + load                         |
| Inrush current, max.   | 1.9 A; Rated value  |
| I <sup>2</sup> t   | 0.34 A <sup>2</sup> ·s                                      |
| <b>Digital inputs</b>  |   |
| <ul style="list-style-type: none"> <li>• from load voltage L+ (without load), max.</li> </ul>                                | 20 mA; per group  |
| <b>Digital outputs</b>   |   |
| <ul style="list-style-type: none"> <li>• from load voltage L+, max.</li> </ul>   | 30 mA; Per group, without load                              |
| <b>Output voltage</b>  |   |
| Rated value (DC)   | 24 V  |
| <b>Encoder supply</b>  |   |
| Number of outputs  | 2; One common 24 V encoder supply per 16 digital inputs     |
| <b>24 V encoder supply</b>   |   |
| <ul style="list-style-type: none"> <li>• 24 V</li> <li>• Short-circuit protection</li> <li>• Output current, max.</li> </ul> | Yes; L+ (-0.8 V)<br>Yes<br>1 A                              |
| <b>Power</b>   |   |
| Infeed power to the backplane bus  | 10 W  |
| Power consumption from the backplane bus (balanced)  | 9 W   |
| <b>Power loss</b>  |   |
| Power loss, typ.   | 15.2 W  |
| <b>Memory</b>  |   |
| Number of slots for SIMATIC memory card  | 1   |
| SIMATIC memory card required   | Yes   |
| <b>Work memory</b>   |   |
| <ul style="list-style-type: none"> <li>• integrated (for program)</li> <li>• integrated (for data)</li> </ul>                | 250 kbyte<br>1 Mbyte  |
| <b>Load memory</b>   |   |
| <ul style="list-style-type: none"> <li>• Plug-in (SIMATIC Memory Card), max.</li> </ul>                                      | 32 Gbyte  |
| <b>Backup</b>  |   |
| <ul style="list-style-type: none"> <li>• maintenance-free</li> </ul>   | Yes   |

## CPU processing times

|                                     |        |
|-------------------------------------|--------|
| for bit operations, typ.            | 48 ns  |
| for word operations, typ.           | 58 ns  |
| for fixed point arithmetic, typ.    | 77 ns  |
| for floating point arithmetic, typ. | 307 ns |

## CPU-blocks

|                            |   |
|----------------------------|---|
| Number of elements (total) | 2 000; Blocks (OB, FB, FC, DB) and UDTs |
|----------------------------|---|

### DB

- Number range: 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999
- Size, max.: 1 Mbyte; For DBs with absolute addressing, the max. size is 64 KB

### FB

- Number range: 0 ... 65 535
- Size, max.: 250 kbyte

### FC

- Number range: 0 ... 65 535
- Size, max.: 250 kbyte

### OB

- Size, max.: 250 kbyte
- Number of free cycle OBs: 100
- Number of time alarm OBs: 20
- Number of delay alarm OBs: 20
- Number of cyclic interrupt OBs: 20; With minimum OB 3x cycle of 500  $\mu$ s
- Number of process alarm OBs: 50
- Number of DPV1 alarm OBs: 3
- Number of isochronous mode OBs: 1
- Number of technology synchronous alarm OBs: 2
- Number of startup OBs: 100
- Number of asynchronous error OBs: 4
- Number of synchronous error OBs: 2
- Number of diagnostic alarm OBs: 1

### Nesting depth

- per priority class: 24

## Counters, timers and their retentivity

### S7 counter

- Number: 2 048

### Retentivity

- adjustable: Yes

### IEC counter

- Number: Any (only limited by the main memory)

|                    |                                       |
|--------------------|---------------------------------------|
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |
| <b>S7 times</b>    |                                       |
| • Number           | 2 048                                 |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |
| <b>IEC timer</b>   |                                       |
| • Number           | Any (only limited by the main memory) |
| <b>Retentivity</b> |                                       |
| — adjustable       | Yes                                   |

### Data areas and their retentivity

|  |  |
|--|--|
| Retentive data area (incl. timers, counters, flags), max.          | 128 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 88 KB |
| Extended retentive data area (incl. timers, counters, flags), max. | 1 Mbyte; When using PS 6 0W 24/48/60 V DC HF   |
| <b>Flag</b>  |  |
| • Number, max.   | 16 kbyte   |
| • Number of clock memories   | 8; 8 clock memory bit, grouped into one clock memory byte  |
| <b>Data blocks</b>   |  |
| • Retentivity adjustable   | Yes  |
| • Retentivity preset   | No   |
| <b>Local data</b>  |  |
| • per priority class, max.   | 64 kbyte; max. 16 KB per block   |

### Address area

|                                     |  |
|-------------------------------------|--|
| Number of IO modules                | 2 048; max. number of modules / submodules     |
| <b>I/O address area</b>             |  |
| • Inputs                            | 32 kbyte; All inputs are in the process image  |
| • Outputs                           | 32 kbyte; All outputs are in the process image |
| <b>per integrated IO subsystem</b>  |  |
| — Inputs (volume)                   | 8 kbyte  |
| — Outputs (volume)                  | 8 kbyte  |
| <b>per CM/CP</b>                    |  |
| — Inputs (volume)                   | 8 kbyte  |
| — Outputs (volume)                  | 8 kbyte  |
| <b>Subprocess images</b>            |  |
| • Number of subprocess images, max. | 32   |

### Hardware configuration

|                                  |   |
|----------------------------------|---|
| Number of distributed IO systems | 32; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| <b>Number of DP masters</b>      |   |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Via CM</li> </ul>                  | 6; A maximum of 6 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total  |
| <b>Number of IO Controllers</b>   |  |
| <ul style="list-style-type: none"> <li>• integrated</li> </ul>              | 1  |
| <ul style="list-style-type: none"> <li>• Via CM</li> </ul>                  | 6; A maximum of 6 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total  |
| <b>Rack</b>   |  |
| <ul style="list-style-type: none"> <li>• Modules per rack, max.</li> </ul>  | 32; CPU + 31 modules   |
| <ul style="list-style-type: none"> <li>• Number of lines, max.</li> </ul>   | 1  |
| <b>PtP CM</b>   |  |
| <ul style="list-style-type: none"> <li>• Number of PtP CMs</li> </ul>       | the number of connectable PtP CMs is only limited by the number of available slots |
| <b>Time of day</b>  |  |
| <b>Clock</b>  |  |
| <ul style="list-style-type: none"> <li>• Type</li> </ul>                    | Hardware clock   |
| <ul style="list-style-type: none"> <li>• Backup time</li> </ul>             | 6 wk; At 40 °C ambient temperature, typically                                      |
| <ul style="list-style-type: none"> <li>• Deviation per day, max.</li> </ul> | 10 s; Typ.: 2 s  |
| <b>Operating hours counter</b>  |  |
| <ul style="list-style-type: none"> <li>• Number</li> </ul>                  | 16   |
| <b>Clock synchronization</b>  |  |
| <ul style="list-style-type: none"> <li>• supported</li> </ul>               | Yes  |
| <ul style="list-style-type: none"> <li>• in AS, master</li> </ul>           | Yes  |
| <ul style="list-style-type: none"> <li>• in AS, slave</li> </ul>            | Yes  |
| <ul style="list-style-type: none"> <li>• on Ethernet via NTP</li> </ul>     | Yes  |
| <b>Digital inputs</b>   |  |
| integrated channels (DI)  | 32   |
| Digital inputs, parameterizable   | Yes  |
| Source/sink input   | P-reading  |
| Input characteristic curve in accordance with IEC 61131, type 3             | Yes  |
| <b>Digital input functions, parameterizable</b>                             |  |
| <ul style="list-style-type: none"> <li>• Gate start/stop</li> </ul>         | Yes  |
| <ul style="list-style-type: none"> <li>• Capture</li> </ul>                 | Yes  |
| <ul style="list-style-type: none"> <li>• Synchronization</li> </ul>         | Yes  |
| <b>Input voltage</b>  |  |
| <ul style="list-style-type: none"> <li>• Type of input voltage</li> </ul>   | DC   |
| <ul style="list-style-type: none"> <li>• Rated value (DC)</li> </ul>        | 24 V   |
| <ul style="list-style-type: none"> <li>• for signal "0"</li> </ul>          | -3 to +5V  |
| <ul style="list-style-type: none"> <li>• for signal "1"</li> </ul>          | +11 to +30V  |
| <b>Input current</b>  |  |
| <ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>    | 2.5 mA   |
| <b>Input delay (for rated value of input voltage)</b>                       |  |

|  |   |
|--|---|
| <b>for standard inputs</b>                       |   |
| — parameterizable                                | Yes; none / 0.05 / 0.1 / 0.4 / 1.6 / 3.2 / 12.8 / 20 ms   |
| — at "0" to "1", min.                            | 4 µs; for parameterization "none"   |
| — at "0" to "1", max.                            | 20 ms   |
| — at "1" to "0", min.                            | 4 µs; for parameterization "none"   |
| — at "1" to "0", max.                            | 20 ms   |
| <b>for interrupt inputs</b>                      |   |
| — parameterizable                                | Yes; Same as for standard inputs  |
| <b>for technological functions</b>               |   |
| — parameterizable                                | Yes; Same as for standard inputs  |
| <b>Cable length</b>                              |   |
| • shielded, max.                                 | 1 000 m; 600 m for technological functions; depending on input frequency, encoder and cable quality; max. 50 m at 100 kHz |
| • unshielded, max.                               | 600 m; for technological functions: No  |
| <b>Digital outputs</b>                           |   |
| Type of digital output                           | Transistor  |
| integrated channels (DO)                         | 32  |
| Current-sourcing                                 | Yes; Push-pull output   |
| Short-circuit protection                         | Yes; electronic/thermal   |
| • Response threshold, typ.                       | 1.6 A with standard output, 0.5 A with high-speed output; see manual for details  |
| Limitation of inductive shutdown voltage to      | Connector X11: -0.8 V; connector X12: L+ (-53 V)  |
| Controlling a digital input                      | Yes   |
| Accuracy of pulse duration                       | Up to ±100 ppm ±2 µs at high-speed output; see manual for details   |
| minimum pulse duration                           | 2 µs; With High Speed output  |
| <b>Digital output functions, parameterizable</b> |   |
| • Switching tripped by comparison values         | Yes; As output signal of a high-speed counter   |
| • PWM output                                     | Yes   |
| — Number, max.                                   | 4   |
| — Cycle duration, parameterizable                | Yes   |
| — ON period, min.                                | 0 %   |
| — ON period, max.                                | 100 %   |
| — Resolution of the duty cycle                   | 0.0036 %; For S7 analog format, min. 40 ns  |
| • Frequency output                               | Yes   |
| • Pulse train                                    | Yes; also for pulse/direction interface   |
| <b>Switching capacity of the outputs</b>         |   |
| • with resistive load, max.                      | 0.5 A; 0.1 A with high-speed output, i.e. when using a high-speed output; see manual for details                          |
| • on lamp load, max.                             | 5 W; 1 W with high-speed output, i.e. when using a high-speed output; see manual for details                              |
| <b>Load resistance range</b>                     |   |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• lower limit</li> </ul>                            | 48 Ω; 240 ohms with high-speed output, i.e. when using a high-speed output; see manual for details                       |
| <ul style="list-style-type: none"> <li>• upper limit</li> </ul>                            | 12 kΩ  |
| <b>Output voltage</b>  |  |
| <ul style="list-style-type: none"> <li>• Type of output voltage</li> </ul>                 | DC   |
| <ul style="list-style-type: none"> <li>• for signal "0", max.</li> </ul>                   | 1 V; With high-speed output, i.e. when using a high-speed output; see manual for details                                 |
| <ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>                   | 23.2 V; L+ (-0.8 V)  |
| <b>Output current</b>  |  |
| <ul style="list-style-type: none"> <li>• for signal "1" rated value</li> </ul>             | 0.5 A; 0.1 A with high-speed output, i.e. when using a high-speed output, observe derating; see manual for details       |
| <ul style="list-style-type: none"> <li>• for signal "1" permissible range, min.</li> </ul> | 2 mA   |
| <ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul> | 0.6 A; 0.12 A with high-speed output, i.e. when using a high-speed output, observe derating; see manual for details      |
| <ul style="list-style-type: none"> <li>• for signal "0" residual current, max.</li> </ul>  | 0.5 mA   |
| <b>Output delay with resistive load</b>  |  |
| <ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>                       | 200 μs   |
| <ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>                       | 500 μs; Load-dependent   |
| <b>for technological functions</b>   |  |
| <ul style="list-style-type: none"> <li>— "0" to "1", max.</li> </ul>                       | 5 μs; Depending on the output used, see additional description in manual   |
| <ul style="list-style-type: none"> <li>— "1" to "0", max.</li> </ul>                       | 5 μs; Depending on the output used, see additional description in manual   |
| <b>Parallel switching of two outputs</b>   |  |
| <ul style="list-style-type: none"> <li>• for logic links</li> </ul>                        | Yes; for technological functions: No   |
| <ul style="list-style-type: none"> <li>• for uprating</li> </ul>                           | No   |
| <ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>        | Yes; for technological functions: No   |
| <b>Switching frequency</b>   |  |
| <ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>              | 100 kHz; For high-speed output, 100 Hz for standard output   |
| <ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>              | 0.5 Hz; Acc. to IEC 60947-5-1, DC-13; observe derating curve   |
| <ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>                     | 10 Hz  |
| <b>Total current of the outputs</b>  |  |
| <ul style="list-style-type: none"> <li>• Current per channel, max.</li> </ul>              | 0.5 A; see additional description in the manual  |
| <ul style="list-style-type: none"> <li>• Current per group, max.</li> </ul>                | 8 A; see additional description in the manual  |
| <ul style="list-style-type: none"> <li>• Current per power supply, max.</li> </ul>         | 4 A; 2 power supplies for each group, current per power supply max. 4 A, see additional description in manual            |
| <b>for technological functions</b>   |  |
| <ul style="list-style-type: none"> <li>— Current per channel, max.</li> </ul>              | 0.5 A; see additional description in the manual  |
| <b>Relay outputs</b>   |  |
| <ul style="list-style-type: none"> <li>• Number of relay outputs</li> </ul>                | 0  |
| <b>Cable length</b>  |  |
| <ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>                         | 1 000 m; 600 m for technological functions; depending on output frequency, load, and cable quality; max. 50 m at 100 kHz |

- unshielded, max.

600 m; for technological functions: No

## Analog inputs

|   |  |
|---|--|
| Number of analog inputs   | 5; 4x for U/I, 1x for R/RTD  |
| <ul style="list-style-type: none"> <li>• For current measurement</li> </ul>                           | 4; max.  |
| <ul style="list-style-type: none"> <li>• For voltage measurement</li> </ul>                           | 4; max.  |
| <ul style="list-style-type: none"> <li>• For resistance/resistance thermometer measurement</li> </ul> | 1  |
| permissible input voltage for voltage input (destruction limit), max.                                 | 28.8 V   |
| permissible input current for current input (destruction limit), max.                                 | 40 mA  |
| Cycle time (all channels), min.   | 1 ms; Dependent on the parameterized interference frequency suppression; for details, see conversion procedure in manual |
| Technical unit for temperature measurement adjustable   | Yes; °C/°F/K   |
| <b>Input ranges (rated values), voltages</b>  |  |
| <ul style="list-style-type: none"> <li>• 0 to +10 V</li> </ul>  | Yes; Physical measuring range: ± 10 V  |
| <ul style="list-style-type: none"> <li>• Input resistance (0 to 10 V)</li> </ul>                      | 100 kΩ   |
| <ul style="list-style-type: none"> <li>• 1 V to 5 V</li> </ul>  | Yes; Physical measuring range: ± 10 V  |
| <ul style="list-style-type: none"> <li>• Input resistance (1 V to 5 V)</li> </ul>                     | 100 kΩ   |
| <ul style="list-style-type: none"> <li>• -10 V to +10 V</li> </ul>                                    | Yes  |
| <ul style="list-style-type: none"> <li>• Input resistance (-10 V to +10 V)</li> </ul>                 | 100 kΩ   |
| <ul style="list-style-type: none"> <li>• -5 V to +5 V</li> </ul>                                      | Yes; Physical measuring range: ± 10 V  |
| <ul style="list-style-type: none"> <li>• Input resistance (-5 V to +5 V)</li> </ul>                   | 100 kΩ   |
| <b>Input ranges (rated values), currents</b>  |  |
| <ul style="list-style-type: none"> <li>• 0 to 20 mA</li> </ul>  | Yes; Physical measuring range: ± 20 mA   |
| <ul style="list-style-type: none"> <li>• Input resistance (0 to 20 mA)</li> </ul>                     | 50 Ω; Plus approx. 55 ohm for overvoltage protection by PTC  |
| <ul style="list-style-type: none"> <li>• -20 mA to +20 mA</li> </ul>                                  | Yes  |
| <ul style="list-style-type: none"> <li>• Input resistance (-20 mA to +20 mA)</li> </ul>               | 50 Ω; Plus approx. 55 ohm for overvoltage protection by PTC  |
| <ul style="list-style-type: none"> <li>• 4 mA to 20 mA</li> </ul>                                     | Yes; Physical measuring range: ± 20 mA   |
| <ul style="list-style-type: none"> <li>• Input resistance (4 mA to 20 mA)</li> </ul>                  | 50 Ω; Plus approx. 55 ohm for overvoltage protection by PTC  |
| <b>Input ranges (rated values), resistance thermometer</b>  |  |
| <ul style="list-style-type: none"> <li>• Ni 100</li> </ul>  | Yes; Standard/climate  |
| <ul style="list-style-type: none"> <li>• Input resistance (Ni 100)</li> </ul>                         | 10 MΩ  |
| <ul style="list-style-type: none"> <li>• Pt 100</li> </ul>  | Yes; Standard/climate  |
| <ul style="list-style-type: none"> <li>• Input resistance (Pt 100)</li> </ul>                         | 10 MΩ  |
| <b>Input ranges (rated values), resistors</b>   |  |
| <ul style="list-style-type: none"> <li>• 0 to 150 ohms</li> </ul>                                     | Yes; Physical measuring range: 0 ... 600 ohms  |
| <ul style="list-style-type: none"> <li>• Input resistance (0 to 150 ohms)</li> </ul>                  | 10 MΩ  |
| <ul style="list-style-type: none"> <li>• 0 to 300 ohms</li> </ul>                                     | Yes; Physical measuring range: 0 ... 600 ohms  |
| <ul style="list-style-type: none"> <li>• Input resistance (0 to 300 ohms)</li> </ul>                  | 10 MΩ  |
| <ul style="list-style-type: none"> <li>• 0 to 600 ohms</li> </ul>                                     | Yes  |



|                                    |                                 |
|------------------------------------|---------------------------------|
| • Input resistance (0 to 600 ohms) | 10 MΩ                           |
| <b>Cable length</b>                |                                 |
| • shielded, max.                   | 800 m; for U/I, 200 m for R/RTD |

### Analog outputs

|  |  |
|--|--|
| integrated channels (AO)                 | 2  |
| Voltage output, short-circuit protection | Yes  |
| Cycle time (all channels), min.          | 1 ms; Dependent on the parameterized interference frequency suppression; for details, see conversion procedure in manual |

### Output ranges, voltage

|                  |     |
|------------------|-----|
| • 0 to 10 V      | Yes |
| • 1 V to 5 V     | Yes |
| • -10 V to +10 V | Yes |

### Output ranges, current

|                    |     |
|--------------------|-----|
| • 0 to 20 mA       | Yes |
| • -20 mA to +20 mA | Yes |
| • 4 mA to 20 mA    | Yes |

### Load impedance (in rated range of output)

|   |        |
|---|--------|
| • with voltage outputs, min.                  | 1 kΩ   |
| • with voltage outputs, capacitive load, max. | 100 nF |
| • with current outputs, max.                  | 500 Ω  |
| • with current outputs, inductive load, max.  | 1 mH   |

### Cable length

|                  |       |
|------------------|-------|
| • shielded, max. | 200 m |
|------------------|-------|

### Analog value generation for the inputs

#### Integration and conversion time/resolution per channel

|  |  |
|--|--|
| • Resolution with overrange (bit including sign), max.                 | 16 bit   |
| • Integration time, parameterizable                                    | Yes; 2.5 / 16.67 / 20 / 100 ms, acts on all channels |
| • Interference voltage suppression for interference frequency f1 in Hz | 400 / 60 / 50 / 10                                   |

#### Smoothing of measured values

|                   |     |
|-------------------|-----|
| • parameterizable | Yes |
| • Step: None      | Yes |
| • Step: low       | Yes |
| • Step: Medium    | Yes |
| • Step: High      | Yes |

### Analog value generation for the outputs

#### Integration and conversion time/resolution per channel

|  |        |
|--|--------|
| • Resolution with overrange (bit including sign), max. | 16 bit |
|--|--------|

#### Settling time

|                       |        |
|-----------------------|--------|
| • for resistive load  | 1.5 ms |
| • for capacitive load | 2.5 ms |
| • for inductive load  | 2.5 ms |

## Encoder

### Connection of signal encoders

|   |     |
|---|-----|
| • for voltage measurement                               | Yes |
| • for current measurement as 4-wire transducer          | Yes |
| • for resistance measurement with two-wire connection   | Yes |
| • for resistance measurement with three-wire connection | Yes |
| • for resistance measurement with four-wire connection  | Yes |

### Connectable encoders

|   |        |
|---|--------|
| • 2-wire sensor                                       | Yes    |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |

### Encoder signals, incremental encoder (asymmetrical)

|  |                                    |
|--|------------------------------------|
| • Input voltage  | 24 V                               |
| • Input frequency, max.  | 100 kHz                            |
| • Counting frequency, max.   | 400 kHz; with quadruple evaluation |
| • Signal filter, parameterizable                                       | Yes                                |
| • Incremental encoder with A/B tracks, 90° phase offset                | Yes                                |
| • Incremental encoder with A/B tracks, 90° phase offset and zero track | Yes                                |
| • Pulse encoder  | Yes                                |
| • Pulse encoder with direction   | Yes                                |
| • Pulse encoder with one impulse signal per count direction            | Yes                                |

## Errors/accuracies

|  |           |
|--|-----------|
| Linearity error (relative to input range), (+/-)                           | 0.1 %     |
| Temperature error (relative to input range), (+/-)                         | 0.005 %/K |
| Crosstalk between the inputs, max.   | -60 dB    |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)  | 0.05 %    |
| Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)     | 0.02 %    |
| Linearity error (relative to output range), (+/-)                          | 0.15 %    |
| Temperature error (relative to output range), (+/-)                        | 0.005 %/K |
| Crosstalk between the outputs, max.  | -80 dB    |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.05 %    |

### Operational error limit in overall temperature range

|  |  |
|--|--|
| • Voltage, relative to input range, (+/-)                | 0.3 %  |
| • Current, relative to input range, (+/-)                | 0.3 %  |
| • Resistance, relative to input range, (+/-)             | 0.3 %  |
| • Resistance thermometer, relative to input range, (+/-) | Pt100 Standard: ±2 K, Pt100 Climate: ±1 K, Ni100 Standard: ±1.2 K, Ni100 Climate: ±1 K |
| • Voltage, relative to output range, (+/-)               | 0.3 %  |
| • Current, relative to output range, (+/-)               | 0.3 %  |

### Basic error limit (operational limit at 25 °C)

|  |  |
|--|--|
| • Voltage, relative to input range, (+/-)                | 0.2 %  |
| • Current, relative to input range, (+/-)                | 0.2 %  |
| • Resistance, relative to input range, (+/-)             | 0.2 %  |
| • Resistance thermometer, relative to input range, (+/-) | Pt100 Standard: ±1 K, Pt100 Climate: ±0.5 K, Ni100 Standard: ±0.6 K, Ni100 Climate: ±0.5 K |
| • Voltage, relative to output range, (+/-)               | 0.2 %  |
| • Current, relative to output range, (+/-)               | 0.2 %  |

### Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency

|  |                         |
|--|-------------------------|
| • Series mode interference (peak value of interference < rated value of input range), min. | 30 dB                   |
| • Common mode voltage, max.  | 10 V                    |
| • Common mode interference, min.   | 60 dB; at 400 Hz: 50 dB |

### Interfaces

|                               |   |
|-------------------------------|---|
| Number of PROFINET interfaces | 1 |
|-------------------------------|---|

### 1. Interface

#### Interface types

|                     |         |
|---------------------|---------|
| • Number of ports   | 2       |
| • integrated switch | Yes     |
| • RJ 45 (Ethernet)  | Yes; X1 |

#### Protocols

|                          |   |
|--------------------------|---|
| • IP protocol            | Yes; IPv4   |
| • PROFINET IO Controller | Yes   |
| • PROFINET IO Device     | Yes   |
| • SIMATIC communication  | Yes   |
| • Open IE communication  | Yes   |
| • Web server             | Yes   |
| • Media redundancy       | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0 |

#### PROFINET IO Controller

##### Services

|                       |     |
|-----------------------|-----|
| — PG/OP communication | Yes |
| — S7 routing          | Yes |
| — Isochronous mode    | Yes |

|   |  |
|---|--|
| — Open IE communication   | Yes  |
| — IRT   | Yes  |
| — MRP   | Yes; as MRP redundancy manager and/or MRP client; max. number of devices in the ring: 50   |
| — MRPD  | Yes; Requirement: IRT  |
| — PROFINergy  | Yes  |
| — Prioritized startup   | Yes; Max. 32 PROFINET devices  |
| — Number of connectable IO Devices, max.                                      | 128; In total, up to 512 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET   |
| — Of which IO devices with IRT, max.  | 64   |
| — Number of connectable IO Devices for RT, max.                               | 128  |
| — of which in line, max.  | 128  |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces  |
| — Number of IO Devices per tool, max.   | 8  |
| — Updating times  | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |

#### Update time for IRT

|  |   |
|--|---|
| — for send cycle of 250 $\mu$ s                      | 250 $\mu$ s to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 625 $\mu$ s of the isochronous OB is decisive |
| — for send cycle of 500 $\mu$ s                      | 500 $\mu$ s to 8 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 625 $\mu$ s of the isochronous OB is decisive |
| — for send cycle of 1 ms                             | 1 ms to 16 ms   |
| — for send cycle of 2 ms                             | 2 ms to 32 ms   |
| — for send cycle of 4 ms                             | 4 ms to 64 ms   |
| — With IRT and parameterization of "odd" send cycles | Update time = set "odd" send clock (any multiple of 125 $\mu$ s: 375 $\mu$ s, 625 $\mu$ s ... 3 875 $\mu$ s)                                  |

#### Update time for RT

|                                 |                       |
|---------------------------------|-----------------------|
| — for send cycle of 250 $\mu$ s | 250 $\mu$ s to 128 ms |
| — for send cycle of 500 $\mu$ s | 500 $\mu$ s to 256 ms |
| — for send cycle of 1 ms        | 1 ms to 512 ms        |
| — for send cycle of 2 ms        | 2 ms to 512 ms        |
| — for send cycle of 4 ms        | 4 ms to 512 ms        |

#### PROFINET IO Device

##### Services

|                         |     |
|-------------------------|-----|
| — PG/OP communication   | Yes |
| — S7 routing            | Yes |
| — Isochronous mode      | No  |
| — Open IE communication | Yes |

|   |  |
|---|--|
| — IRT   | Yes  |
| — MRP   | Yes; as MRP redundancy manager and/or MRP client; max. number of devices in the ring: 50 |
| — MRPD  | Yes; Requirement: IRT  |
| — PROFinergy  | Yes; per user program  |
| — Shared device                                     | Yes  |
| — Number of IO Controllers with shared device, max. | 4  |
| — Asset management record                           | Yes; per user program  |

## Interface types

### RJ 45 (Ethernet)

|                   |     |
|-------------------|-----|
| • 100 Mbps        | Yes |
| • Autonegotiation | Yes |
| • Autocrossing    | Yes |

## Protocols

### Number of connections

|   |   |
|---|---|
| • Number of connections, max.                     | 128; via integrated interfaces of the CPU and connected CPs / CMs |
| • Number of connections reserved for ES/HMI/web   | 10  |
| • Number of connections via integrated interfaces | 88  |
| • Number of S7 routing paths                      | 16  |

### Redundancy mode

|                     |     |
|---------------------|-----|
| • H-Sync forwarding | Yes |
|---------------------|-----|

### SIMATIC communication

|                               |  |
|-------------------------------|--|
| • S7 communication, as server | Yes  |
| • S7 communication, as client | Yes  |
| • User data per job, max.     | See online help (S7 communication, user data size) |

### Open IE communication

|   |  |
|---|--|
| • TCP/IP  | Yes                                    |
| — Data length, max.                               | 64 kbyte                               |
| — several passive connections per port, supported | Yes                                    |
| • ISO-on-TCP (RFC1006)                            | Yes                                    |
| — Data length, max.                               | 64 kbyte                               |
| • UDP   | Yes                                    |
| — Data length, max.                               | 2 kbyte; 1 472 bytes for UDP broadcast |
| — UDP multicast                                   | Yes; Max. 5 multicast circuits         |
| • DHCP  | No                                     |
| • SNMP  | Yes                                    |
| • DCP   | Yes                                    |

|  |   |
|--|---|
| • LLDP   | Yes   |
| <b>Web server</b>  |   |
| • HTTP   | Yes; Standard and user pages  |
| • HTTPS  | Yes; Standard and user pages  |
| <b>OPC UA</b>  |   |
| • Runtime license required   | Yes   |
| • OPC UA client  | Yes   |
| — Application authentication   | Yes   |
| — Security policies  | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication  | "anonymous" or by user name & password  |
| — Number of connections, max.  | 4   |
| — Number of nodes of the client interfaces, max.   | 1 000   |
| — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList, max.   | 300   |
| — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max.  | 20  |
| — Number of elements for one call of OPC-UA_MethodGetHandleList, max.  | 100   |
| — Number of simultaneous calls of the client instructions per connection (except OPC-UA_ReadList, OPC-UA_WriteList, OPC-UA_MethodCall), max. | 1   |
| — Number of simultaneous calls of the client instructions<br>OPC-UA_ReadList, OPC-UA_WriteList and OPC-UA_MethodCall, max.                   | 5   |
| — Number of registerable nodes, max.   | 5 000   |
| — Number of registerable method calls of OPC-UA_MethodCall, max.   | 100   |
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max.  | 20  |
| • OPC UA server  | Yes; Data access (read, write, subscribe), method call, custom address space    |
| — Application authentication   | Yes   |
| — Security policies  | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication  | "anonymous" or by user name & password  |
| — Number of sessions, max.   | 32  |
| — Number of accessible variables, max.   | 50 000  |
| — Number of registerable nodes, max.   | 10 000  |
| — Number of subscriptions per session, max.  | 20  |

|   |  |
|---|--|
| — Sampling interval, min.                                       | 100 ms   |
| — Publishing interval, min.                                     | 500 ms   |
| — Number of server methods, max.                                | 20   |
| — Number of inputs/outputs per server method, max.              | 20   |
| — Number of monitored items, max.                               | 1 000; for 1 s sampling interval and 1 s send interval                               |
| — Number of server interfaces, max.                             | 10   |
| — Number of nodes for user-defined server interfaces, max.      | 1 000  |
| <b>Further protocols</b>  |  |
| • MODBUS  | Yes; MODBUS TCP  |
| <b>Media redundancy</b>   |  |
| • Switchover time on line break, typ.                           | 200 ms; For MRP, bumpless for MRPD   |
| • Number of stations in the ring, max.                          | 50   |
| <b>Isochronous mode</b>   |  |
| Isochronous operation (application synchronized up to terminal) | Yes; With minimum OB 6x cycle of 625 µs (distributed)                                |
| Equidistance  | Yes  |
| <b>S7 message functions</b>                                     |  |
| Number of login stations for message functions, max.            | 32   |
| Program alarms  | Yes  |
| Number of configurable program messages, max.                   | 5 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH |
| Number of loadable program messages in RUN, max.                | 2 500  |
| Number of simultaneously active program alarms                  |  |
| • Number of program alarms                                      | 300  |
| • Number of alarms for system diagnostics                       | 100  |
| • Number of alarms for motion technology objects                | 80   |
| <b>Test commissioning functions</b>                             |  |
| Joint commission (Team Engineering)                             | Yes; Parallel online access possible for up to 5 engineering systems                 |
| Status block  | Yes; Up to 8 simultaneously (in total across all ES clients)                         |
| Single step   | No   |
| Number of breakpoints   | 8  |
| <b>Status/control</b>   |  |
| • Status/control variable                                       | Yes  |
| • Variables   | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters                 |
| • Number of variables, max.                                     |  |
| — of which status variables, max.                               | 200; per job   |

|  |  |
|--|--|
| — of which control variables, max.   | 200; per job   |
| <b>Forcing</b>   |  |
| • Forcing, variables   | Peripheral inputs/outputs  |
| • Number of variables, max.  | 200  |
| <b>Diagnostic buffer</b>   |  |
| • present  | Yes  |
| • Number of entries, max.  | 1 000  |
| — of which powerfail-proof   | 500  |
| <b>Traces</b>  |  |
| • Number of configurable Traces  | 4; Up to 512 KB of data per trace are possible   |
| <b>Interrupts/diagnostics/status information</b>   |  |
| <b>Alarms</b>  |  |
| • Diagnostic alarm   | Yes  |
| • Hardware interrupt   | Yes  |
| <b>Diagnostic messages</b>   |  |
| • Monitoring the supply voltage  | Yes  |
| • Wire-break   | Yes; for analog inputs/outputs, see description in manual  |
| • Short-circuit  | Yes; for analog outputs, see description in manual   |
| • A/B transition error at incremental encoder  | Yes  |
| <b>Diagnostics indication LED</b>  |  |
| • RUN/STOP LED   | Yes  |
| • ERROR LED  | Yes  |
| • MAINT LED  | Yes  |
| • STOP ACTIVE LED  | Yes  |
| • Monitoring of the supply voltage (PWR-LED)   | Yes  |
| • Channel status display   | Yes  |
| • for channel diagnostics  | Yes; For analog inputs/outputs   |
| • Connection display LINK TX/RX  | Yes  |
| <b>Supported technology objects</b>  |  |
| Motion Control   | Yes; Note: The number of axes affects the cycle time of the PLC program; selection guide via the TIA Selection Tool or SIZER |
| • Number of available Motion Control resources for technology objects (except cam disks) | 800  |
| • Required Motion Control resources  |  |
| — per speed-controlled axis  | 40   |
| — per positioning axis   | 80   |
| — per synchronous axis   | 160  |
| — per external encoder   | 80   |
| — per output cam   | 20   |
| — per cam track  | 160  |
| — per probe  | 40   |



|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Positioning axis               <ul style="list-style-type: none"> <li>— Number of positioning axes at motion control cycle of 4 ms (typical value)</li> <li>— Number of positioning axes at motion control cycle of 8 ms (typical value)</li> </ul> </li> </ul>         | <p>5</p> <p>10</p>   |
| <b>Controller</b> <ul style="list-style-type: none"> <li>• PID_Compact</li> <li>• PID_3Step</li> <li>• PID-Temp</li> </ul>   | <p>Yes; Universal PID controller with integrated optimization</p> <p>Yes; PID controller with integrated optimization for valves</p> <p>Yes; PID controller with integrated optimization for temperature</p> |
| <b>Counting and measuring</b> <ul style="list-style-type: none"> <li>• High-speed counter</li> </ul>   | <p>Yes</p>   |
| <b>Integrated Functions</b>  |  |
| Number of counters   | 6  |
| Counting frequency (counter) max.  | 400 kHz; with quadruple evaluation   |
| <b>Counting functions</b>  |  |
| <ul style="list-style-type: none"> <li>• Continuous counting</li> <li>• Counter response parameterizable</li> <li>• Hardware gate via digital input</li> <li>• Software gate</li> <li>• Event-controlled stop</li> <li>• Synchronization via digital input</li> <li>• Counting range, parameterizable</li> </ul> | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>   |
| <b>Comparator</b>  |  |
| <ul style="list-style-type: none"> <li>— Number of comparators</li> <li>— Direction dependency</li> <li>— Can be changed from user program</li> </ul>  | <p>2; per count channel; see manual for details</p> <p>Yes</p> <p>Yes</p>  |
| <b>Position detection</b>  |  |
| <ul style="list-style-type: none"> <li>• Incremental acquisition</li> <li>• Suitable for S7-1500 Motion Control</li> </ul>   | <p>Yes</p> <p>Yes</p>  |
| <b>Measuring functions</b>   |  |
| <ul style="list-style-type: none"> <li>• Measuring time, parameterizable</li> <li>• Dynamic measurement period adjustment</li> <li>• Number of thresholds, parameterizable</li> </ul>  | <p>Yes</p> <p>Yes</p> <p>2</p>   |
| <b>Measuring range</b>   |  |
| <ul style="list-style-type: none"> <li>— Frequency measurement, min.</li> <li>— Frequency measurement, max.</li> <li>— Cycle duration measurement, min.</li> <li>— Cycle duration measurement, max.</li> </ul>   | <p>0.04 Hz</p> <p>400 kHz; with quadruple evaluation</p> <p>2.5 <math>\mu</math>s</p> <p>25 s</p>  |
| <b>Accuracy</b>  |  |
| <ul style="list-style-type: none"> <li>— Frequency measurement</li> <li>— Cycle duration measurement</li> </ul>  | <p>100 ppm; depending on measuring interval and signal evaluation</p> <p>100 ppm; depending on measuring interval and signal evaluation</p>  |

— Velocity measurement

100 ppm; depending on measuring interval and signal evaluation

## Potential separation

### Potential separation digital inputs

- between the channels No
- between the channels, in groups of 16

### Potential separation digital outputs

- between the channels No
- between the channels, in groups of 16

### Potential separation channels

- between the channels and backplane bus Yes
- Between the channels and load voltage L+ No

## Isolation

Isolation tested with 707 V DC (type test)

## Ambient conditions

### Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 60 °C; Note derating data for onboard I/O in the manual. Display: 50 °C, at an operating temperature of typically 50 °C, the display is switched off
- vertical installation, min. 0 °C
- vertical installation, max. 40 °C; Note derating data for onboard I/O in the manual. Display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off

### Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

### Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

## Configuration

### Programming

#### Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- GRAPH Yes

### Know-how protection

- User program protection/password protection Yes
- Copy protection Yes
- Block protection Yes

### Access protection

- |   |     |
|---|-----|
| • Password for display                    | Yes |
| • Protection level: Write protection      | Yes |
| • Protection level: Read/write protection | Yes |
| • Protection level: Complete protection   | Yes |

### Cycle time monitoring

- |               |                               |
|---------------|-------------------------------|
| • lower limit | adjustable minimum cycle time |
| • upper limit | adjustable maximum cycle time |

### Dimensions

|        |        |
|--------|--------|
| Width  | 110 mm |
| Height | 147 mm |
| Depth  | 129 mm |

### Weights

|                 |         |
|-----------------|---------|
| Weight, approx. | 1 360 g |
|-----------------|---------|

**last modified:** 08/30/2019