

SIPLUS S7-300 SM321 - 20-POLE -40 ... +70°C with conformal coating conformity with EN50155 T1 KAT 1 KL A/B based on 6ES7321-1BH02-0AA0. DIGITAL INPUT OPTIC. ISOLATED 16 DI, 24V DC, 1 X 20-POLE



### Supply voltage

#### Load voltage L+

- |                                       |        |
|---------------------------------------|--------|
| • Rated value (DC)                    | 24 V   |
| • permissible range, lower limit (DC) | 20.4 V |
| • permissible range, upper limit (DC) | 28.8 V |

### Input current

from backplane bus 5 V DC, max.	10 mA
---------------------------------	-------

### Power loss

Power loss, typ.	3.5 W
------------------	-------

### Digital inputs

Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes

#### Number of simultaneously controllable inputs

horizontal installation	
— up to 40 °C, max.	16
— up to 60 °C, max.	16; 16 @ > 60 °C

vertical installation	
-----------------------	--

— up to 40 °C, max.	16
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	13 to 30V
<b>Input current</b>	
• for signal "1", typ.	7 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
<b>Alarms</b>	
• Diagnostic alarm	No
• Hardware interrupt	No
<b>Diagnostics indication LED</b>	
• Status indicator digital input (green)	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
• between the channels	No
• between the channels, in groups of	16
• between the channels and backplane bus	Yes; Optocoupler
<b>Permissible potential difference</b>	
between different circuits	75 V DC/60 V AC

Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
• ATEX	Yes
Railway application	
• EN 50155	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C; = Tmin
• max.	70 °C; = Tmax; 60 °C @ UL/cUL, ATEX and FM use
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *

— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
<b>Remark</b>	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!

#### Connection method

required front connector	20-pin
--------------------------	--------

#### Dimensions

Width	40 mm
Height	125 mm
Depth	120 mm

#### Weights

Weight, approx.	200 g
-----------------	-------

**last modified:** 08/31/2019