

SIPLUS S7-300 SM 322 8DO 48-125V -25...+70°C with conformal coating based on 6ES7322-1CF00-0AA0 . Digital output isolated, 8 DO, 48-125 V DC, 1.5A, 1x 20-pole



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	48 V; 48 V DC to 125 V DC
• permissible range, lower limit (DC)	40 V
• permissible range, upper limit (DC)	140 V
Input current	
from load voltage L+ (without load), max.	2 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	7.2 W
Digital outputs	
Number of digital outputs	8
Limitation of inductive shutdown voltage to	M (-1 V)
Switching capacity of the outputs	
• on lamp load, max.	15 W; 15 W (48 V) or 40 W (125 V)
Output voltage	

• for signal "1", min.	L+ (-1.2 V)
Output current	
• for signal "1" rated value	1.5 A
• for signal "1" minimum load current	10 mA
• for signal "1" permissible surge current, max.	3 A; for 10 ms
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	25 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	6 A
— up to 60 °C, max.	3 A
— up to 70 °C, max.	1 A
vertical installation	
— up to 40 °C, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Alarms	
• Diagnostic alarm	No
Diagnostic messages	
• Wire-break	No
• Short-circuit	No
• Fuse blown	No
• missing load voltage	No
Diagnostics indication LED	
• Rated load voltage PWR (green)	No
• Fuse OK FSG (green)	No
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
• between the channels	Yes
• between the channels, in groups of	4
• between the channels and backplane bus	Yes; Optocoupler
Permissible potential difference	

between different circuits	146 V DC/132 V AC
Isolation	
Isolation tested with	1500 V AC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
• EN 50155	Yes; T1 Category 1 Class A/B horizontal mounting position
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	70 °C; = Tmax; for use on railway vehicles according to EN50155, the rated temperature range -25 ... +55 °C (T1) or 60 °C @ UL/ULhaz/ATEX/FM use applies
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	

— Against chemically active substances acc. to EN 60654-4

Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Connection method

required front connector

20-pin

Dimensions

Width

40 mm

Height

125 mm

Depth

120 mm

Weights

Weight, approx.

250 g

last modified:

08/31/2019