

Product type designation

SIPLUS NET CP 343-1

SIPLUS NET CP 343-1 -25...+70 °C with conformal coating based on 6GK7343-1EX30-0XE0 . Communications processor for connection of SIMATIC S7-300 to Industrial Ethernet via ISO and TCP/IP, PROFINET IO controller or PROFINET IO device, Integrated 2-port switch ERTEC 200, S7 communication, fetch/write, Send/Receive with and without RFC1006, MULTICAST DHCP, NTC-CPU Sync, diagnostics, initialization via LAN, 2x RJ45 connection for LAN with 10/100 Mbit/s



Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

2

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

2

1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet
- of Industrial Ethernet interface
- for power supply

RJ45 port

RJ45 port

2-pole plugable terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

24 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.2 A
• from external supply voltage / at DC / at 24 V / typical	0.16 A
• from external supply voltage / at DC / at 24 V / maximum	0.2 A
Power loss [W]	5.8 W

Ambient conditions

Ambient temperature	
• during operation	-25 ... +70 °C
• for horizontally arranged busbars / during operation	-25 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• in horizontal mounting position / during operation	70 ... -25 °C
• during storage and transport	70 ... -40 °C
Installation altitude / at height above sea level / maximum	5000 m
Relative humidity	
• with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
• with condensation / acc. to IEC 60068-2-38 / maximum	100 %
Resistance to biologically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes
• conformity acc. to EN 60721-3-6	Yes
Coating / for equipped printed circuit board / acc. to EN 61086	Yes
Type of coating / protection against pollution according to EN 60664-3	Yes
Type of test / of the coating / acc. to MIL-I-46058C	Yes
Product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes

Protection class IP	IP20
Design, dimensions and weight	
Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.22 kg
Performance data / open communication	
Number of Multicast stations	16
Performance data / S7 communication	
Number of possible connections / for S7 communication	
• maximum	16
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	32
Performance data / PROFINET communication / as PN IO-Controller	
Number of external PN IO lines / with PROFINET / per rack	1
Amount of data	
• as user data for input variables / as PROFINET IO controller / maximum	1 Kibyte
• as user data for input variables / as PROFINET IO controller / maximum	1 Kibyte
• as user data for input variables per PN IO device / as PROFINET IO controller / maximum	240 byte
• as user data for output variables per PN IO device / as PROFINET IO controller / maximum	240 byte
Performance data / PROFINET communication / as PN IO-Device	
Amount of data	
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / as PROFINET IO device / maximum	512 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for input variables / for each sub-module as PROFINET IO device	240 byte
• as user data for the consistency area for each sub-module	240 byte
Number of submodules / per PROFINET IO-Device	32

Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.4 SP2 or higher
Product functions / switch	
Product feature / Switch	Yes
Product function	
<ul style="list-style-type: none"> • with IRT / PROFINET IO switch 	Yes
<ul style="list-style-type: none"> • Configuration with STEP 7 	Yes
Product functions / Redundancy	
Product function	
<ul style="list-style-type: none"> • Ring redundancy 	Yes
<ul style="list-style-type: none"> • Redundancy manager 	No
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product functions / Security	
Product function	
<ul style="list-style-type: none"> • ACL - IP-based 	Yes
<ul style="list-style-type: none"> • ACL - IP-based for PLC/routing 	No
<ul style="list-style-type: none"> • switch-off of non-required services 	Yes
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • NTP 	Yes
Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
Security information	

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

08/26/2019