Data sheet



Compact Switch Module CSM 377 Connection SIMATIC S7-300 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s unmanaged switch, 4 RJ45 ports, External 24 V DC power supply LED diagnostics, S7-300 module, incl. electron. Equipment Manual on CD-ROM

| Product type designation | SCALANCE CSM 377 |
|--|-----------------------|
| Transmission rate | |
| Transfer rate | 10 Mbit/s, 100 Mbit/s |
| Interfaces / for communication / integrated | |
| Number of electrical connections | |
| for network components or terminal equipment | 4 |
| Number of 100 Mbit/s SC ports | |
| • for multimode | 0 |
| Number of 1000 Mbit/s LC ports | |
| • for multimode | 0 |
| • for single mode (LD) | 0 |
| Interfaces / others | |
| Number of electrical connections | |
| • for power supply | 1 |
| Type of electrical connection | |
| • for power supply | 2-pole terminal block |
| Supply voltage, current consumption, power loss | |

| Type of voltage / of the supply voltage | DC |
|---|------------------------------|
| Supply voltage | |
| • external | 24 V |
| • external / minimum | 19.2 V |
| • external / maximum | 28.8 V |
| Product component / fusing at power supply input | Yes |
| Fuse protection type / at input for supply voltage | 0.5 A / 60 V |
| Consumed current / maximum | 0.07 A |
| Power loss [W] | |
| • at DC / at 24 V | 1.6 W |
| Permitted ambient conditions | |
| Ambient temperature | |
| during operation | 0 60 °C |
| during storage | -40 +70 °C |
| during transport | -40 +70 °C |
| Relative humidity | |
| at 25 °C / without condensation / during | 95 % |
| operation / maximum | |
| Protection class IP | IP20 |
| Design, dimensions and weight | |
| Design | SIMATIC S7-300 device design |
| Width | 40 mm |
| Height | 125 mm |
| Depth | 118 mm |
| Net weight | 0.2 kg |
| Mounting type | |
| • 35 mm DIN rail mounting | No |
| wall mounting | No |
| • S7-300 rail mounting | Yes |
| • S7-1500 rail mounting | No |
| Draduct functions / management, configuration | |
| Product functions / management, configuration Product function | |
| multiport mirroring | No |
| Product function / switch-managed | No |
| _ | |
| Product functions / Redundancy Product function | |
| | Yes |
| Parallel Redundancy Protocol (PRP)/operation in the PRP-network | 1 03 |
| | |
| Parallel Redundancy Protocol | No |
| | No |

Standard

FM3611: Class 1, Divison 2, Group A, B, C, D / T.., CL.1, Zone 2, • for FM

GP. IIC, T.. Ta

• for hazardous zone EN 60079-15, II 3 G Ex nA II T.., KEMA 06 ATEX 0021 X

UL 508, CSA C22.2 No. 142 • for safety / from CSA and UL

• for hazardous zone / from CSA and UL UL 1604 and UL 2279-15 (Hazardous Location)

EN 61000-6-4:2001 • for emitted interference

• for interference immunity EN 61000-6-2:2001

Standards, specifications, approvals / CE

Certificate of suitability / CE marking

Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability EN 61000-6-2:2001, EN 61000-6-4:2001

• C-Tick

 KC approval No

Standards, specifications, approvals / ship classification

Marine classification association

• American Bureau of Shipping Europe Ltd. Yes

(ABS)

Yes Bureau Veritas (BV)

Yes • Det Norske Veritas (DNV)

• Germanische Lloyd (GL) No

• Lloyds Register of Shipping (LRS) Yes

Yes • Nippon Kaiji Kyokai (NK)

• Polski Rejestr Statkow (PRS) No

• Royal Institution of Naval Architects (RINA) No

Standards, specifications, approvals / product conformity

MTBF 144 y

Further Information / Internet Links

Internet-Link

http://www.siemens.com/snst • to website: Selector SIMATIC NET

SELECTION TOOL

http://www.siemens.com/simatic-net • to website: Industrial communication

https://mall.industry.siemens.com • to website: Industry Mall

http://www.siemens.com/industry/infocenter • to website: Information and Download Center

http://automation.siemens.com/bilddb • to website: Image database

• to website: CAx Download Manager http://www.siemens.com/cax

• to website: Industry Online Support https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

08/27/2019